

STANDARD

BETEX GIANT 40, 48, 100 kVA

AREAS OF APPLICATION:

- Chemical industry
- Steel industry
- Paper industry
- Gearbox manufacturers
- Machine building
- Transport sector
- MRO/OEM sector
- Wind energy
- Power plants
- Mining industry

Heavy duty heaters.

- Min. ID Ø: 85/215 mm
- Max. OD Ø: 1400-2500 mm
- Max. width: 440-990 mm
- Automatic demagnetisation
- Automatic power reduction
- Yokes: selection of 5 sizes
- Max. bearing weight: 1500-3500 kg
- Max. weight other parts: 900-2500 kg

Optional:

- electric crane
- enlarged width 700 mm: DL700
- enlarged width 1000 mm: DL1000

NB: these technical data are indicative and dependent on the amount of power and type of heater.

Technical details page 32



Heating times are subject to the relationship between:

- Min. bore and max. outside diameter, width, weight.
- Required temperature and material type.
- Available power.

TURBO

BETEX GIANT TURBO 40, 48, 100 kVA

AREAS OF APPLICATION:

- Chemical industry
- Steel industry
- Paper industry
- Gearbox manufacturers
- Machine building
- Transport sector
- MRO/OEM sector
- Wind energy
- Power plants
- Mining industry

Heavy duty heaters.

- Min. ID Ø: 115 - 240 mm
- Max. OD Ø: 1400-2500 mm
- Max. width: 450-1020 mm
- Automatic demagnetisation
- Automatic power reduction
- Including 1 yoke
- Max. bearing weight: 1500-12000 kg
- Max. weight other parts: < 12000 kg

NB: these technical data are indicative and dependent on the amount of power and type of heater.

Technical details page 32



✓ High output, energy efficient!



The TURBO effect only works when the component is in a horizontal position